

Acryl Exterior +

How to order

Acryl Exterior+ is available in 310 ml cartridges packed per 12 in a box. To order your specific Acryl Exterior+, please find below the article and EAN codes:

Colour:	Article code:	EAN code:
White	10760002	8711595139229
Grey	10685001	8711595087216
Brown	10685101	8711595087209



Centre of Excellence

Better results through Knowledge

Den Braven 's company payoff is "Better results through Knowledge". Our Centre of Excellence accumulates knowledge which provides her with the latest market insights, developments and trends. This knowledge is shared within the Den Braven Group and amongst our customers and end-users.

This process enables our relations to achieve higher efficiency and better results. This is the true meaning of "Better results through Knowledge". Visit our website to discover more about what the Centre of Excellence could mean for you!



Den Braven



Acryl Exterior +

Rain resistant acrylic sealant for outside use

Acryl Exterior+

Rain resistant acrylic sealant for outside use

- Early rain resistant
- Suitable for outside* use
- High elongation at break
- High movement accommodation
- Paintable with water based- and synthetic paints
- Perfect adhesion even on slightly damp substrates
- Nearly non smelling
- Easy to apply and clean
- Non corrosive towards metals



Acryl Exterior+

Product Descriptions

Acryl Exterior+ is a high quality acrylic sealant, early rain resistant after application. After application the product forms a soft plasto elastic rubber by evaporation of water from the sealant.

Applications

Acryl Exterior+ has been especially developed for connection joints between windowsills, stairs, ceilings, walls, metal sheets, thresholds, panels, aerated concrete, plasterboard, lime-stone, wooden and metal window frames, concrete and brickwork for interior and exterior applications. As the sealant is early rain resistant after application there are less application limitations because of weather conditions.



Acryl Exterior+

Certifications

EN 15651-1: F-EXT-INT 12,5P

Technical Performances

Density	1,57 g/ml
Shore-A hardness	10°
Elongation at break	600%
Skin formation	10 minutes

Visit our website to download the full technical specifications of the Acryl Exterior+.

* Acryl Exterior+ is early rain resistance but during application and curing both surface and weather conditions should be dry.



Visit Den Braven YouTube channel

Den Braven offers a wide variety of USP, Application and Commercial movies via here website and YouTube channel. Scan the below displayed QR Code to visit the USP movie of the original Acryl Exterior+:

